

File No.: E01- 6428/19/97

ReTender

Date : 06/02/21

**Notice Inviting Tender / e-Tender / Quotation**

Thrissur Corporation Electricity Department invites sealed quotation / open tenders / e-Tenders from eligible applicants, who fulfill the qualification criteria as stipulated in the Store Purchase Manual Kerala, Kerala PWD Code & LGSD Tender regulations for the Supply / Work mentioned in the below-tabulation sheet.

The details of the Tender are as per following :


Approximate Cost of Supply / Work	:	3,46,172/- with GST
Supply / Work Description	:	Pin Insulator, Shackle strain set etc
Tender Security / EMD / Amt.	:	3500/-
Cost of Tender Form	:	695+83+7
Tender Document on Sale	:	
A.S. approved by	:	37 <sup>th</sup> Council Resolution on 4/5/20
T.S. approved by	:	
Last Date & Time of issuing Tender Form	:	
Last Date & Time of Submitting Tender	:	2/3/2021 2pm
Date & Time of Opening Tender	:	4/03/2021 3pm
Authority & Place for submit of Tender	:	Electricity Department, Thrissur Corporation - 680001

- \* Sale of Tender form available only after 2. P.M. everyday once tender floated.
- \* Applicants must have GST Registration
- \* Quoted rate should be inclusive of relevant Taxes
- \* Tender inviting officer shall have every right to revoke tender / quotation at any time without any reason
- \* Those who participate in work tender should own concerned electrical contract licence.

Assistant Secretary

**GROUP VII INSULATORS & ACCESSORIES****Detailed Requirement - Annual Purchase 2020-21**

Sl No	Item	Unit	Rate	Specification	Quantity	Amount
1	Pin Insulator LT with rod	Nos	85	Porcelain insulators for overhead power lines with nominal voltage upto and including 1000V as per IS 1445-1977 with GI pin and suitable for fixing in 75mm channel Iron X arm	120	10200
3	Shackle 4*4 1/2 with clamp	Nos	190	Porcelain 1100V shackle insulator, 100*112.5mm, along with two number of GI bolt & nut(12.5*15mm) and suitable straps required for the shackle.	600	114000
4	Strain Set with Disc insulator	Nos	973	11KV HT Disc insulator along with hardware, twisted straps, connecting sockets split pin assembly complete.	100	97300
5	Post Top insulator	Nos	696	Post type porcelain insulator rated voltage 12kv,As per IS:2544 with the creeping distance 25mm/kv min.Top of insulator should be 80mm dia and with PCD 57mm,rated short time withstand current for one second shall be 16kA and the rated peak withstand current shall be 40kA.	152	105792
6	11KV Disc insulator	Nos	472	11 KV HT Disc without hardware	40	18880
	<b>Total</b>					<b>346172</b>

  
**ELECTRICAL ENGINEER**  
JOSE T.S.  
Electrical Engineer  
Electricity Department  
Thrissur Corporation  
Tel: 23559